## **Bally**®

## **QUOTE REQUEST FORM**

This form is the first step to creating your customized Bally Walk-In Cooler/Freezer with up to 3 compartments. *(If your Walk-In requires more than 3 compartments, you do not need to fill out the form just email us or call 1-800-24BALLY.)* Please fill out this form, adding any comments or questions, and email it to sales@ballyrefboxes.com.

A Bally representative will contact you with information and help you find a dealer in your area.

Name:		Email:						
Business Name:		Project Name:						
Address:		City:	State Zip					
Phone:		Fax:						
<b>OVERALL DIMENSIONS of WALK-IN</b> 4" Panel 5" Panel 6" Panel								
Estimated LENGTH:	Estimated WIDTH:		Estimated HEIGHT:					
*Choose from: 5'10", 6'3¾", 6'9½", 7'3¼", 7'9", 8'2¾", 8'8½", 9'2¼", 9'8", 10'1¾", 10'7½", 11'1¼", 11'7", 12'0¾", 12'6½", 13'0¼", 13'6", 14'5½", 15'5", 16'4½", 17'4", 18'3½", 19'3", 20'2½". Lon- ger buildings are available in additional 5¾" increments.	7'9", 8'2¾", 8'8½", 10'7½", 11'1¼", 11 13'0¼", 13'6", 14'	", 6'3¾", 6'9½", 7'3¼", 9'2¼", 9'8", 10'1¾", 1'7", 12'0¾", 12'6½", 5½". Longer build- in additional 11½"	*Choose from: 6'6", 7'6", 8'6", 9'6", 10'6" (Single length verticals) Taller buildings are available in additional 12" increments, with stacked vertical pan- els. Heights shown are with floor; subtract 4" for less-floor units.					
*Non-Standard dimensions can expect longer lead times.								
Number of Compartments? (Check one)   1   2   3   Other   Instant	Height of Building (if against one):        '        '         Number of Walls         Size        x         Hand sketch of the cooler/freezer							
Comments:	For Bally	y Use Only:						
	Other	ox Price:						
Exterior Finish: (Check one)  Stucco-embossed Galvalume Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White alur Stucco-embossed Sand-tan g Stucco-embossed White galv Sandex Stone-textured Galva Embossed Stainless	eel ninum galvanized steel vanized steel	<ul> <li>Stucco-emb</li> <li>Smooth Wh</li> <li>Stainless ster</li> <li>Stucco-emb</li> <li>Stucco-emb</li> <li>Stucco-emb</li> <li>Stucco-emb</li> <li>Stucco-emb</li> </ul>	<ul> <li>Interior Finish: (Check one)</li> <li>Stucco-embossed Galvalume steel</li> <li>Smooth White galvanized steel</li> <li>Stainless steel</li> <li>Stucco-embossed aluminum</li> <li>Stucco-embossed White aluminum</li> <li>Stucco-embossed White galvanized steel</li> <li>Smooth White aluminum</li> <li>Embossed Stainless</li> </ul>					

FLOORS	Floor Types: (Check one) Less Floor W/ Floor W/ Floor—Less Floor Light Use—Foot Traffic Medium Use—Hand Truck or Small Cart Heavy Duty—Structurally Reinforced (Keg or Pallet Jack & Queen Mary)				<ul> <li>Floor Panel Finishes: (Check one)</li> <li>3/16" Aluminum Diamond Tread Overlay</li> <li>.100 ga. Smooth Aluminum</li> <li>16 ga. Stainless Steel</li> <li>Rigidized Aluminum Diamond Pattern</li> <li>1/8" Aluminum Diamond Tread</li> <li>Rigidized Stainless Steel Diamond Pattern</li> <li>16 ga. Galvanized Steel (Non NSF - to be used under any NSF approved Overlay)</li> <li>Extra Overlay: 3/16" Diamond Tread</li> </ul>							
RAMPS       ROOFS - Options: (Check one)         None       Interior         Exterior       Membrane roof w/ tapered insulation         No roof, indoor Walk-in												
	-	No. of Doors:           Uidth:			Door Options: Observation Window in Entrance Door: 14" x 14" Deadbolt Handle Latch: (K27C) Strip Curtain(s)							
		Door 2	Width: Choose from: 30", 36", 42", 48", 54", 60"	Č	Height: Choose from: 66", 78", 84"		Super Doors (1/8" Diamondtread kickplate on both sides, 3 <sup>rd</sup> hinge. Standard Sizes; included unless noted)					
	<b>ב</b>	Door 3	Width: Choose from: 30", 36", 42", 48", 54", 60"	Ċ	Height: Choose from: 66", 78", 84"		Glass Display Doors: Number of Doors: Size: x					
	Additional Doors:			Sliding Door: Qty Size: x Slide Direction: Left Right								
ACCESSORIES												
Pressure Relief Port (required for freezers)AdditionalPartition Walls (location)YesFree Standing ShelvingIf yes:				No Modularm 75L C WEISS		Modularm 75L C WEISS						
<b>REFRIGERATION SYSTEMS</b> Storage Only Product Load												
Compartment 1	Cor	nder	tion <i>(Choose one)</i> : poler	Compartment 2	Condensi	ler [ ng Ur oor Re door <i>f</i> Conta		Compartment 3	Application (Choose one): Cooler Freezer Condensing Unit: Indoor Remote Outdoor Air-Cooled Remote Self-Contained (PT-Unit) Indoor Water Cooled			

Notes: For line sets  $\leq 75'$ 

SmartVap+ Evaporator Controls are Standard at Bally.